

L-823 Secondary Cable Assemblies

Certified to FAA AC 150/5345-26 (Current Edition)

Provide reliable connections in the harshest conditions



Specifications

- Manufactured by Amerance or Integro
- Constructed of rugged thermoplastic rubber for long-lasting, reliable service



Style 1

Style 6

Style 7

Style 8

General Catalog Numbers

95M-□-□-□.□

Available in 1/2 meter increments to any length.

Connector(s)

- P Style 1 Plug
- P6 Style 6 Plug
- R7 Style 7 Receptacle
- R8 Style 8 Receptacle

For connectors on both ends use two codes, otherwise one.

Cable

- F** Two individual #12 AWG (3,3mm²) thermoplastic insulated, waterproof wires, rated 600 volts between contacts, 1500 volts to earth, 20 amp, 90°C. O.D. 4,7mm (.185")
- G** 2/12 AWG (3,3mm²) thermoplastic insulated waterproof cable with overall jacket, rated 600 volts between contacts, 1500 volts to earth, 20 amp, 90°C. O.D. 12,7mm (.5")
- H** Two individual #16 AWG (1,3mm²) thermoplastic insulated, waterproof wires, rated 600 volts between contacts, 1500 volts to earth, 20 amp, 90°C. O.D. 3,2mm (.125")
- I** 2/16 AWG (1,3mm²) thermoplastic insulated waterproof cable with overall jacket, rated 600 volts between contacts, 1500 volts to earth, 20 amp, 90°C. O.D. 9,4mm (.37")
- K** Two individual #14 AWG (2,1mm²) Teflon insulated wires, rated 600 volts between contacts, 1500 volts to earth, 20 amp, 200°C, wires certified to UL1199 and CSA1A/B
- L** As K above except #16 AWG (1,3mm²)