



L-853 Airport Marking System

Certified to FAA AC 150/5345-39 (Current Edition)

Superior long term performance and corrosion resistance

Highlights

- Manufactured by Safe-Hit
- Reboundable, self restoring design keeps life cycle costs among the lowest in the industry
- Constructed of co-extruded polyethylene with UV inhibitors -no above ground metal parts
- High intensity retroreflective sheeting for excellent visibility in all lighting conditions
- Surface mount on asphalt or concrete; soil anchor versions also available
- Post integrated quick-install locking pins

Specifications

Reflective Colors: Blue, Silver, Red or Green
 Post Height: 14", 18", 24" or 30" [36cm, 46cm, 61cm or 76cm]
 Reflective Length: 14" [36cm]
 Post Color: White
 Post Diameter: 2¼" [57mm]
 Base Diameter: 8" [20cm]
 Standard Soil Anchor Length: 18" [46cm]
 Inner Tube Reinforcement Diameter: 1¾" [44mm]

SMA=Surface Mount A=Pin Lock
 GP3=Soil Anchor T=Twist Lock

SH6-□□ □□□ □ □□□
 SH6-□□ □□□

Height
 14=14"
 18=18"
 24=24"
 30=30"

Reflective Color
 B=Blue
 S=Silver
 R=Red
 G=Green

Example: SH6-24-SMA-W-R-14 is an L-853 Marker
 24" high surface mount with red reflective color

12=only used on 14" OAH
 14=used on all other heights

